

# EXA100

## Stereo Integrated Amplifier



<b>POWER OUTPUT</b>	100W RMS into 8 Ohms
<b>AMPLIFICATION</b>	Class-A/B
<b>DAC</b>	ES9018K2M
<b>FREQUENCY RESPONSE</b>	<3Hz – >40kHz +/-1dB
<b>TOROIDAL TRANSFORMER</b>	Yes
<b>PREAMP MODE</b>	Yes
<b>BI-WIRING POSSIBLE</b>	Yes
<b>ANALOGUE RCA INPUTS</b>	3 x pair
<b>BALANCED XLR INPUTS</b>	1 x pair
<b>HDMI ARC</b>	Yes - eARC compatible PCM up to 24bit/192kHz
<b>ASYNCHRONOUS USB</b>	1 x Type B conforming to Audio Class 1 or 2 (user selectable). Audio Class 1: Up to 24-bit 96kHz Audio Class 2: Up to 24-bit 384kHz / DSD-256
<b>S/PDIF TOSLINK INPUT</b>	1 x 16/24-bit 32-96kHz
<b>S/PDIF COAXIAL INPUT</b>	1 x 16/24-bit 32-192kHz
<b>BLUETOOTH</b>	5.0 A2DP/AVRCP supporting SBC, aptX and aptX HD codecs
<b>RS232 CONTROL</b>	Yes
<b>PREAMP OUTPUT</b>	Yes - 1 x RCA
<b>HEADPHONE OUTPUT</b>	Yes
<b>SUBWOOFER OUTPUT</b>	Yes - 1 x RCA
<b>SPEAKER OUTPUTS</b>	2 x pair
<b>MAX POWER CONSUMPTION</b>	1200w
<b>STANDBY POWER CONSUMPTION</b>	<0.5W
<b>DIMENSIONS (W X H X D)</b>	115 x 430 x 341mm (4.5 x 16.9 x 13.4")
<b>WEIGHT</b>	12.8kg (28.2Lbs)
<b>WHAT'S IN THE BOX</b>	Power cords, Remote control, Welcome letter, Registration Card, Safety guide